

GS 0492 F

AMENDMENTS TO THE CLAIMS

The listing below of the claims will replace all prior versions and listings of claims in the present application:

Listing of Claims:

Claim 1 (canceled)

Claim 2 (currently amended): A transmission ~~according to claim 1~~, for a motor vehicle, said transmission comprising: a plurality of sets of gears defining transmission ratio steps, wherein each set of gears includes a first gear non-rotatably connected with a first shaft and an idler gear connected with a second shaft, whereby transmission ratio steps are engaged by connecting an idler gear with a first gear by means of a final output element that is part of a final output mechanism and that is actuated by the final output mechanism with which a shaft bearing said element is connected, and whereby a shift sequence of the transmission ratio steps is not established in the final output mechanism, a plurality of side-by-side shift rails for shifting gear steps, and a stop rail operatively engageable with the shift rails for selectively blocking a shift rail to prevent unintended engagement or disengagement of a gear group, and in which the final output mechanism includes at least one primary actuation element which enters into an operative connection with the final output mechanisms such that a transmission ratio step is engageable using a first final output mechanism and the at least one primary actuation element then can enter into operative

GS 0492 F

connection with another final output mechanism without having to disengage a previously engaged transmission ratio step, wherein the final output mechanism includes at least one secondary actuation ~~mechanism~~ element.

Claim 3 (previously presented): A transmission according to claim 2, wherein as soon as the at least one primary actuation element enters into interaction with a final output mechanism, the at least one secondary actuation element can enter into interaction with at least one further final output mechanism.

Claim 4 (previously presented): A transmission according to claim 3, wherein the at least one further final output mechanism is associated with a still engaged transmission ratio step.

Claim 5 (previously presented): A transmission according to claim 3, wherein upon actuation of a final output mechanism for engaging a transmission ratio step using the at least one primary actuation element, at the same time at least one additional final output mechanism is actuated using at least the one secondary actuation element for disengaging the associated transmission ratio steps.

Claim 6 (previously presented): A transmission according to claim 3, wherein, when one gear is engaged, at least one gear not engaged is prevented

GS 0492 F

from an unintended engagement using the at least one secondary actuation element if the primary actuation element of the engaged gear remains in the region of an end position, which establishes the engagement of the gear.

Claim 7 (previously presented): A transmission according to claim 2, wherein only one transmission ratio step is engageable at a time through the at least one primary actuation element.

Claim 8 (previously presented): A transmission according to claim 2, in which the transmission ratio steps form groups between which a tractive force interruption-free change can take place, wherein as soon as the at least one primary actuation element enters into operative connection with the final output mechanism of a group, the at least one secondary actuation element can enter into operative connection with at least one further final output mechanism of the same group.

Claim 9 (previously presented): A transmission according to claim 8, wherein the at least one further final output mechanism of the same group is associated with a still engaged transmission ratio step.

Claim 10 (previously presented): A transmission according to claim 8, wherein when one final output mechanism of a group is actuated for engaging a transmission ratio step using the at least one primary actuation element, at the

GS 0492 F

same time at least one further final output mechanism of the same group is actuated using the at least one secondary actuation element for disengaging the associated transmission ratio steps.

Claim 11 (previously presented): A transmission according to claim 8, wherein as soon as the at least one primary actuation element enters into operative connection with a final output mechanism of a group, the at least one secondary actuation element enters into operative connection with no final actuation mechanism of the other group.

Claim 12 (previously presented): A transmission according to claim 8, wherein in any given case, when one gear of a group is engaged, at least one gear of this group which is not engaged is prevented from an unintended engagement using the at least one secondary actuation element if the primary actuation element of the engaged gear of this group remains in the region of the end position which fixes the engagement of this gear.

Claim 13 (previously presented): A transmission according to claim 8, wherein in any given case only one transmission ratio step is engageable at a time in each group.

Claim 14 (previously presented): A transmission according to claim 2, wherein the at least one primary actuation element is rotatable with restriction in

GS 0492 F

relation to the at least one secondary actuation element against the action of an energy storage unit.

Claim 15 (previously presented): A transmission according to claim 3, wherein when a final output mechanism is actuated, the synchronization of an idler gear of a newly to be engaged transmission ratio step begins using the at least one primary actuation element before at least one further final output mechanism is actuated using the at least one secondary actuation element for disengaging the associated transmission ratio steps.

Claim 16 (previously presented): A transmission according to claim 15, wherein using the at least one secondary actuation element, the disengagement of the associated transmission ratio step takes place before the synchronization of the one idler gear is ended and the engagement of the newly to be engaged transmission ratio step takes place using the primary actuation element.

Claim 17 (previously presented): A transmission according to claim 16, wherein when one gear is engaged, at least one gear not engaged is prevented from an unintended engagement using the at least one secondary actuation element if the primary actuation element of the engaged gear remains in the region of the end position, which fixes the engagement of the gear.

Claim 18 (previously presented): A transmission according to claim 16,

GS 0492 F

wherein the motion of the primary actuation element for engaging the newly to be engaged transmission ratio step is prevented by a blocking device controlled by the secondary actuation element, whereby the secondary actuation element blocks the blockage device until the engaged transmission ratio step is disengaged.

Claim 19 (previously presented): A transmission according to claim 2, wherein the final output mechanisms include connection elements including at least one of shift forks or selector shafts and forks, which have a first functional area for the engagement of a primary actuation element and a second functional area for the engagement of a secondary actuation element.

Claim 20 (previously presented): A transmission according to claim 19, in which the at least one secondary actuation element is arranged on a selector shaft rotatable about its longitudinal axis when actuated, and in which the second functional area is constructed such that when the selector shaft is rotated, a force from one secondary actuation element can be transferred to the second functional area in the direction of disengagement of the associated transmission ratio step, which is equal to or greater than the force necessary for disengagement.

Claim 21 (previously presented): A transmission according to claim 2, wherein at least one actuation element can be brought into operative connection

GS 0492 F

with one or more final output mechanisms at the same time.

Claim 22 (previously presented): A transmission according to claim 21, wherein the at least one secondary actuation element has a breadth in the direction of the selector shaft so that at least two final output mechanisms can be acted upon at the same time.

Claim 23 (currently amended): A transmission according to claim ~~2~~ 19, wherein the at least one secondary actuation element and the second functional areas interact such that a disengagement of a transmission ratio step takes place when the selector shaft rotates, independent of the direction of rotation of the latter.

Claim 24 (currently amended): A transmission in accordance with claim 23, wherein the at least one secondary actuation element and the second functional ~~regions~~ areas are constructed symmetrically with relation to a plane erected on the selector shaft.

Claim 25 (previously presented): A transmission according to claim 23, wherein the at least one secondary actuation element has two cam-like end regions and the second functional regions have recesses corresponding therewith.

GS 0492 F

Claim 26 (previously presented): A transmission according to claim 23, wherein the second functional regions have two cam-like end regions and the at least one secondary actuation element has recesses corresponding therewith.

Claim 27 (previously presented): A transmission according to claim 23, wherein the force transmission between secondary actuation element and the second functional area takes place via the tips of cam-like end regions.

Claim 28 (previously presented): A transmission according to claim 23, wherein the transmission of force between secondary actuation element and the second functional region takes place via the lateral surfaces of the cam-like end regions.

Claim 29 (currently amended): A transmission according to claim 4 2, wherein ~~the~~ at least one transmission actuator unit formed from a shift actuator and a selection actuator ~~with a~~ is mounted on at least one final actuation output mechanism as a separate subassembly can be mounted on a pre-assembled transmission comprising having an opening for access of the final actuation mechanism to the at least one final output mechanism.

Claim 30 (currently amended): A transmission according to claim 4 2, wherein a transmission actuation unit ~~comprised of~~ including a manually actuated selector element and a manually actuated shift element ~~with a~~ with a is mounted

GS 0492 F

~~on at least one final actuation~~ output mechanism as a separate subassembly can ~~be mounted~~ on a pre-assembled transmission ~~comprising~~ having an opening for access ~~of the final actuation mechanism~~ to at least one final output mechanism.

Claim 31 (currently amended): A transmission according to claim 29, wherein the ~~same~~ opening is utilized for access to the transmission actuator unit and ~~for~~ to the transmission actuation unit.

Claim 32 (previously presented): A transmission according to claim 29, wherein the transmission actuator unit and the transmission actuation unit use the same final output mechanisms for engaging and disengaging transmission ratio steps.

Claim 33 (currently amended): A transmission according to claim 23, wherein the final ~~actuation~~ output mechanism ~~is comprised of~~ includes a primary actuation element, which engages ~~basically~~ substantially free of play ~~into~~ with the at least one final output element while forming an involute engagement and actuates said at least one final output element.

Claim 34 (currently amended): A transmission according to claim 29, wherein the final ~~actuation~~ output mechanism ~~is comprised of~~ includes a primary actuation element, which engages substantially without play ~~into~~ with the at least one final output mechanism and actuates it.

GS 0492 F

Claim 35 (currently amended): A transmission according to claim 34, wherein the substantially play-free ~~intervention~~ engagement is an involute engagement.

Claim 36 (currently amended): A transmission according to claim 2, wherein at least one of the at least one primary ~~and/or~~ and secondary actuation ~~element~~ elements interacts with at least one final output element while forming an involute engagement.

Claim 37 (previously presented): A transmission according to claim 2, wherein the at least one primary and one secondary actuation element are one piece.

Claim 38 (previously presented): A transmission according to claim 37, wherein at least one primary actuation element is enclosed along its axis of rotation by two secondary actuation elements and in that primary and secondary actuation elements are constructed in one piece.

Claim 39 (previously presented): A transmission according to claim 37, wherein at least one of the primary or secondary actuation elements is one piece with the selector shaft accommodating them.

GS 0492 F

Claim 40 (previously presented): A transmission according to claim 26, wherein the at least one primary actuation element and at least one secondary actuation element exert an involute engagement on a single shift jaw, whereby for the at least one primary actuation element and for the at least one secondary actuation element a separate involute region is provided in each case.

Claim 41 (currently amended): A transmission according to claim 4 2, wherein the engagement of one transmission ratio step takes place according to a linear path relationship between the final output element and a primary actuation element.

Claim 42 (currently amended): A transmission according to claim 4 2, wherein the engagement of a transmission ratio step takes place in accordance with a non-linear path relationship between the final output element and a primary actuation element.

Claim 43 (currently amended): A transmission according to claim 4 2, wherein the disengagement of a transmission ratio step takes place according to a linear relationship between the final output element and a secondary actuation element.

Claim 44 (currently amended): A transmission according to claim 4 2, wherein ~~the~~ disengagement of a transmission ratio step takes place in

GS 0492 F

accordance with a non-linear path relationship between the final output element and a secondary actuation element.

Claim 45 (currently amended): A transmission according to claim 4 2, wherein an engagement motion of a transmission ratio step to be engaged and a disengagement motion of a transmission ratio step to be disengaged overlap.

Claim 46 (currently amended): A transmission according to claim 4 2, wherein an engagement motion of a transmission ratio step to be engaged and a disengagement motion of a transmission ratio step to be disengaged do not overlap.

Claim 47 (currently amended): A transmission according to claim 4 2, wherein a selection motion for positioning the at least one primary actuation mechanism on an end output mechanism is a displacement of ~~it~~ the at least one primary actuation mechanism along an axis of rotation and a shifting motion is a rotary motion of the at least one primary actuation element about ~~this~~ that axis of rotation.

Claim 48 (currently amended): A transmission according to claim 4 2, wherein a selection motion for positioning the at least one primary actuation element on ~~an~~ a final output mechanism takes place by means of a rotary motion about an axis of rotation and a shifting motion by means of a displacement along

GS 0492 F

this that axis of rotation.

Claim 49 (currently amended): A transmission according to claim 48, wherein a final actuation mechanism is constructed such that a hollow shaft rotatable about an axis of rotation has at least one radially outwardly projecting primary actuation element, and that in the hollow shaft a forced control penetrating through slots in the hollow shaft is provided for two secondary actuation elements arranged on the hollow shaft with radially extended impingement facilities for the final output elements, which arranges the secondary actuation elements during a displacement of the hollow shaft along the axis of rotation at a limited distance from one another, whereby the final output mechanisms are arranged across at least one peripheral segment around the axis of rotation of the hollow shaft, and in a first displacement of the hollow shaft within the limited distance [[,]] the secondary actuation elements disengage an engaged gear, and with a further displacement of the hollow shaft beyond the limited distance the at least one primary actuation element engages a newly to be engaged gear [[,]] after the at least one primary actuation element and the final output mechanism ~~were~~ are brought into the same peripheral position for the new gear to be engaged by means of a rotation of the hollow shaft.

Claim 50 (currently amended): A transmission according to claim 49, wherein two primary actuation elements are ~~arranged across the periphery~~ peripherally positioned and activate a group of final output mechanisms ~~in any~~

GS 0492 F

~~given case.~~

Claim 51 (currently amended): A transmission according to claim 49, wherein ~~long~~ elongated slots are provided in the secondary actuation elements along which the primary actuation elements are guided upon a displacement of the hollow shaft.

Claim 52 (currently amended): A transmission according to claim 48, wherein both secondary actuation elements ~~is~~ are pre-stressed.

Claim 53 (currently amended): A transmission according to claim 2, wherein in the transmission ~~[[,]]~~ at least one transmission brake is provided for braking a transmission input shaft, which brake is actuated ~~using~~ by one of a primary ~~or~~ and a secondary actuation element.

Claim 54 (currently amended): A transmission according to claim 4 2, wherein the final output element ~~forms two groups with a distance regarded~~ includes two rotatable actuation elements spaced from each other along an axis of rotation ~~of their direction of action~~ about which they act.

Claim 55 (currently amended): A transmission according to claim 4 2, wherein at least one final output element is tapered from radially inward to radially outward in an area of an operating engagement with at least one of the

GS 0492 F

primary ~~and/or~~ and a secondary actuation element in relation to the an axis of rotation of the at least one primary ~~and/or~~ and secondary actuation element ~~rotating that rotates~~ during a shift process.

Claim 56 (currently amended): A transmission according to claim 4 2, wherein, independently of the position of the final output elements, the at least one primary actuation element ~~can be brought~~ is movable into the a neutral position (N) in which all engaged gears are disengaged through the at least one secondary actuation element.

Claim 57 (previously presented): A transmission in accordance with claim 56, wherein the neutral position is reached by means of a selection motion of the at least one primary actuation element beyond the final output elements and a subsequent shifting motion.

Claim 58 (currently amended): A transmission according to claim 56, wherein the neutral position (N) is provided in a final output mechanism [[.]] which actuates only one gear, and ~~the~~ a shifting motion for setting the neutral position takes place opposite to the a shifting motion for actuation of the final output element ~~shifted by the latter~~.

Claim 59 (previously presented): A transmission according to claim 56, wherein the neutral position is reached using a selection motion of the primary

GS 0492 F

actuation element between two final output elements and a subsequent shifting motion.

Claim 60 (currently amended): A transmission according to claim 4 2, wherein a selection process ~~fixing~~ for establishing a position of a final output mechanism for a newly to be engaged transmission ratio step takes place immediately before disengaging an engaged transmission ratio step, and includes engaging a the newly to be engaged transmission ratio step during a reduction phase of a drive torque furnished by a drive unit in a power branch of the motor vehicle.

Claim 61 (currently amended): A transmission according to claim 4 2, wherein the transmission includes at least two power branches each having one transmission input shaft, and idler gears rotatable thereon, which are connectable with ~~the~~ associated transmission input shafts using the final output mechanisms for shifting gears, whereby during the operation of the motor vehicle using a first transmission input shaft and a shifted gear corresponding to the driving situation, a following gear is engaged with a transmission ratio step fitting the driving situation on a second transmission input shaft.

Claim 62 (previously presented): A transmission according to claim 61, wherein the following transmission ratio step is the next higher transmission ratio step in relation to the reduction engaged on the first transmission input shaft.

GS 0492 F

Claim 63 (previously presented): A transmission according to claim 61, wherein, during a standstill of the vehicle, a transmission ratio step is engaged on each of the transmission input shafts by means of which the motor vehicle can be started.

Claim 64 (previously presented): A transmission according to claim 63, wherein a transmission ratio step with which the motor vehicle can be started up is a reverse gear or a forward gear.

Claim 65 (previously presented): A transmission according to claim 61, wherein when the driving situation changes, the following transmission ratio step is changed.

Claim 66 (currently amended): A transmission according to claim 61, wherein, corresponding to the driving situation, a final output mechanism is selected using a primary actuation element, but is not actuated, which corresponds to the an alternative transmission ratio step ~~alternative of the likely a~~ following transmission ratio step.

Claim 67 (currently amended): A transmission according to claim 66, wherein the alternative transmission ratio step corresponds to a transmission ratio step with greater reduction during a partial load operation of the motor

GS 0492 F

vehicle ~~than that with which~~ the motor vehicle is then being operated ~~at this time~~, whereby with this greater reduction in during full load operation, ~~the maximal~~ maximum acceleration of the motor vehicle can be attained.

Claim 68 (currently amended): A transmission according to claim 66, wherein the alternative transmission ratio step at a full load operation of the motor vehicle corresponds to a transmission ratio step with a smaller reduction than that with which the motor vehicle is then being operated ~~at this point in time~~, whereby with ~~this~~ the smaller reduction ~~[[,]]~~ the motor vehicle is economically operable ~~in an especially economical~~ during partial load operation.

Claim 69 (currently amended): A transmission according to claim 60, wherein after a selection of the final output element, at least one of the primary and/or and secondary actuation element ~~elements~~ acts upon at least one final output element of a transmission ratio step to be disengaged , and in such manner that a disengagement process of ~~this~~ the transmission ratio step to be disengaged only takes place when a torque acting on the final output element connecting ~~the~~ an idler gear with a transmission shaft is near zero.